

THE BLAZE 40 & 60E

Empowered by Innovative engineering



	240V/480V	600V
60KW	144/72AMPS	58 AMPS
40KW	96/48AMPS	39 AMPS
20KW	48/24AMPS	19.5 AMPS

FEATURES

- ✓ Up to 4,500 CFM, 3" of Static Pressure allows for up to 50 feet of ducting overall with max of 12 feet on return.
- ✓ Recirculating Capabilities
- ✓ Indicator lamps for Power On. Remote thermostat capabilities. Fan manual override.
- ✓ Digital Temperature Controller. Able to set discharge temperature
- ✓ 51.5" X 22" X 35.5" 300lbs
- ✓ Blaze 40E (20/40kw)
Blaze 60E (40/60kw)

480/240V easy
switchover toggle
switch feature

Available in 600 Volts/3PH and
480V/240V/3PH

HEAT SETTING	BTU/Hr.	CFM
60kW	205,000	4,500
40kW	136,500	4,500
20kW	68,250	4,500

Max Outlet Temperature=290° F

High Performance Portable Heating

Efficient, Reliable, Safe & Easy to Service

Added Features

- ✓ Operates at extremely low noise levels
- ✓ Unique High Static Fan allows recirculation of warm inside air, resulting in even temperatures and energy savings
- ✓ Durable Heating Element designed for the most demanding environments
- ✓ Ask about how our Heaters can help you with your next LEED construction project
- ✓ Forklift pockets, and removable casters for easy lifting and placement
- ✓ Rugged, weatherproof enclosures for reliable operation outdoors
- ✓ Stackable for off-Season Storage
- ✓ Clean electric heat, free from the moisture and fumes associated with other types of heat
- ✓ Certified for use in the U.S. and Canada